

Contents

Preface to English Edition — IX

Preface — XI

Part I: Devices containing a single-link pendulum

- 1 A pendulum with stationary pivot — 5**
 - 1.1 Equations of motion — 5
 - 1.2 Domain of controllability — 7
 - 1.3 Maximizing domain of attraction — 9
 - 1.4 Delay in feedback loop — 13
 - 1.5 Nonlinear control — 16
 - 1.6 Controllability domain of the nonlinear model — 17

- 2 A pendulum with wheel-based pivot — 21**
 - 2.1 Equations of motion — 21
 - 2.2 Domain of controllability — 24
 - 2.3 Maximizing domain of attraction — 27
 - 2.4 Nonlinear control — 29

- 3 A pendulum with a flywheel — 31**
 - 3.1 The arrangement of the pendulum with a flywheel — 31
 - 3.2 Equations of motion — 33
 - 3.3 Local stabilization of the pendulum in the top equilibrium — 35
 - 3.4 Suppressing flywheel rotation — 41
 - 3.5 Swinging and damping the pendulum — 42
 - 3.6 Translating the pendulum from the bottom equilibrium into the top one — 45
 - 3.7 Numerical experiments — 46
 - 3.8 Practical experiments — 47

- 4 Wheel rolling control by means of a pendulum — 50**
 - 4.1 Mathematical model — 51
 - 4.2 Steady modes of motion — 53
 - 4.3 Stability of steady-state modes — 56

- 5 Optimal swinging and damping of a swing — 58**
 - 5.1 On optimal control design in second-order systems — **58**
 - 5.2 Mathematical model of a swing — **62**
 - 5.3 Maximizing the swing oscillations magnitude — **63**
 - 5.4 Minimizing swing oscillation magnitude — **67**
 - 5.5 Controlling a swing with regard for aerodynamic resistance and dry friction — **69**

- 6 Pendulum control that minimizes energy consumption — 71**
 - 6.1 Estimation of energy consumption — **71**
 - 6.2 Translating the pendulum to the unstable equilibrium — **74**
 - 6.3 Translating the pendulum to the stable equilibrium — **80**

Part II: Double physical pendulum

- 7 Local stabilization of an inverted pendulum by means of a single control torque — 91**
 - 7.1 Mathematical model of the pendulum — **91**
 - 7.2 Linearized model — **93**
 - 7.3 Domains of controllability — **94**
 - 7.4 Feedback design. Maximizing domain of attraction — **98**
 - 7.5 Numerical experiments — **104**

- 8 Optimal control design for swinging and damping a double pendulum — 110**
 - 8.1 Mathematical model — **110**
 - 8.2 Reduced angle — **112**
 - 8.3 Optimal control that swings the pendulum — **113**
 - 8.4 Optimal control law for pendulum damping — **119**
 - 8.5 On translating the pendulum from its bottom equilibrium to the top one — **123**

- 9 Global stabilization of an inverted pendulum controlled by torque in the inter-link joint — 126**
 - 9.1 Mathematical model — **127**
 - 9.2 Cascade form of dynamic equations — **128**
 - 9.3 Control law that swings the pendulum — **129**
 - 9.4 Tracking the desired inter-link angle dynamics — **130**
 - 9.5 Local stabilization of an inverted pendulum — **131**
 - 9.6 Numerical experiments — **131**

10 Global stabilization of an inverted pendulum controlled by torque in the pivot — 134

- 10.1 Mathematical model — 134
- 10.2 Swinging the pendulum — 135
- 10.3 Straightening the pendulum — 135
- 10.4 Linear model, local stabilization — 138
- 10.5 Numerical experiments — 141

11 Multi-link pendulum on a moving base — 145

- 11.1 Multi-link pendulum on a wheel — 145
- 11.2 Single-link pendulum on a wheel — 149
- 11.3 Global stabilization of the inverted pendulum — 151
- 11.4 Domain of controllability — 155
- 11.5 Designing time-optimal trajectories — 157
- 11.6 A pendulum on a cart — 159
- 11.7 Frequency lowering as a result of constraining — 161

Part III: Ball on a beam

12 Stabilization of a ball on a straight beam — 165

- 12.1 Mathematical model of the system — 165
- 12.2 Linearized model — 167
- 12.3 Feedback design — 169
- 12.4 Numerical experiments — 171

13 Stabilization of a ball on a curvilinear beam — 176

- 13.1 Mathematical model of the system — 176
- 13.2 Linearized model — 178
- 13.3 Feedback design — 180
- 13.4 Numerical experiments — 181

Part IV: Gyroscopic stabilization of a two-wheel bicycle

14 Bicycle design — 189

- 14.1 Bicycle with one controlled wheel — 189
- 14.2 Bicycle with two controlled wheels — 192
- 14.3 Gyroscopic stabilizer — 194
- 14.4 Equations of tilt oscillations of the bicycle — 195

- 15 Designing a control law to stabilize the bicycle tilt — 198**
- 15.1 Bicycle tilt measurement by means of accelerometers — 198
- 15.2 Bicycle movement along a straight line — 199
- 15.3 Motion along a circle — 201
- 15.4 Numerical and practical experiments — 203

Part V: **Avoiding undesired vibrations**

- 16 Bang-bang control and fluent control — 209**
- 16.1 Mathematical model — 210
- 16.2 Formulation of the problem — 212
- 16.3 Bang-bang control versus fluent control — 213

- 17 Trapezoidal control for a system with compliant elements — 217**
- 17.1 Trapezoidal fluent control — 217
- 17.2 Trapezoidal control with shorter transients — 220
- 17.3 Relationship between time T and displacement x_d — 223
- 17.4 Numerical analysis of the open-loop system — 224
- 17.5 Feedback control — 227

Bibliography — 229

Index — 237